


FLUID PENDANT LAMP – EU VERSION

CLAESSON KOIVISTO RUNE ON THE DESIGN "We wanted to give the lamp a form with a certain softness, towards a more natural language and further removed from pure geometry. Fascinated by the way that surface tension governs the curvature of a resting water droplet, we have tried to capture it's essence. The subtle irregularity of Fluid means that their silhouette gently changes depending upon the viewing angle. It also brings a greater light intensity to the lamps'underside - just where you need it."



42 cm 16.5"




23 cm 9"

CEILING CAP



Ø II cm / 4.25"



DESIGNED BY / YEAR OF DESIGN

Claesson Koivisto Rune / 2011 & 2013

ABOUT THE DESIGNER

Claesson Koivisto Rune is one of Swedens most prominent design studios and the three designers have among many international awards been awarded the annual Swedish design award eight times.

CATEGORY

Pendant lamp

ENVIRONMENT

Indoor

DESCRIPTION

Fluid Pendant Lamp is a modern pendant with personality and ambience. Place the lamp alone over a table, or mix small and large Fluid lamps. Arrange in rows or clusters to create a cosy atmosphere δ beautiful light.

PRODUCTION PROCESS

The Fluid lampshade is made from mouth blown glass, which is frosted silky mat. The edge on top of the lamp is grinded and polished.

MATERIAL

White silk mat opal glass, lid in Nylon66 with fibre glass.

CORD LENGTH

350 cm /137.75"

BULB INCLUDED

Large: No Small: Yes

CEILING CAP INCLUDED

Yes - White

DIMMABLE FUNCTION


Larae: Yes

Small: Yes, if dimmable bulb is used.

CLEANING AND CARE

Clean with soft dry cloth only. Always switch off the electricity supply before cleaning.





FLUID PENDANT LAMP – EU VERSION









IP20









LAMP RATING - SMALL

 Voltage
 220-240VV

 Frequency
 50/60Hz

 IP Rating
 IP20

 Classification
 Class II

 Socket
 I x G9

Max. 40W; Halogen Max. 5W; LED bulb

LAMP RATING - LARGE

 Voltage
 22O-24OVV

 Frequency
 5O/6OHz

 IP Rating
 IP2O

 Classification
 Class II

 Socket
 I x E27

 Max. 6OW

Max. 13W PL Lamp (self-ballasted) Max. 18W LED bulb

BULB SPECIFICATION - SMALL

Item G9 LED bulb
Watt 3W
Lumen 23OIm
Kelvin 27OOK
Lifetime 25.OOOh
CRI >8O
Dimmable No

BULB RECOMMENDATION - SMALL

Lamp baseG9DimensionsØ20 X 60 mmLight source shapeFrostedMax wattageSee ratingLight source typeLED

BULB RECOMMENDATION - LARGE

Lamp base E27

Dimensions Ø60 X 110 mm

Light source shapeA60Max wattageSee ratingLight source typeLED

GENERAL STANDARDS & CERTIFICATES - SMALL

 EU/UK
 CHINA
 TAIWAN

 CE-LVD
 CCC
 BSMI

 EN 60598-I:2008+AII:2009
 GB7000. 20I-2008
 CNSI4II5

 EN 62493:20IO
 IEC60598/2/4

 WEEE
 CNSI4335

GENERAL STANDARDS & CERTIFICATES - LARGE

EU/UK	GERMANY	AUSTRALIEN/NEW ZEALAND	TAIWAN
CE-LVD	VDE	RCM	BSMI
EN 60598-1:2008+AII:2009	Certificate for Socket	AS/NZS 60238:2007	
EN 60598-2-1:1989	DIN EN 60238 (VDE 0616 Teil	CNSI4II5	
	1):2009-04	IEC6O598/2/4	
WFFF	FN 60938:9004+AI:9008-09	CNSI4335	

MUUTO