



Hula 46. Counter stool with upholstered shell and injection swivel central base finished in different colors.

0.206 m3 7.27 Ft 7.2 kg 15.87 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	870	680	460	515

Frame	Injected aluminium swivel central base. Rotating system integreted into top of the structure. Injected aluminum plate fixes the base to the seat. Felt glides.
Seat	Upholstered seat with flame retardant polyurethane flexible foam with a density between 25 kg/m3 and 40 kg/m4
Back	Upholstered back with flame retardant polyurethane flexible foam with a density between 25 kg/m3 and 40 kg/m4
Accesories	Felt glide.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

- Leather / Piel**
L1 High grade cow leather
 Piel de vaca de 1ª categoría
L3 Polished full grain leather
 Plena flor pulida
L6 Aniline leather batique-effect.
 Scandinavian cattle.
 Piel anilina efecto batique.
 Ganado escandinavo.

Leather



Aluminum finish

RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	FSC ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard